


# 裸端子 丸形 (R形) [R1.25~R5.5]



品番 Catalog No.	規格 Standards	適合ねじ径 Stud Size	適合電線範囲 Wire Size	寸法 (mm) Dimensions							入り数 Qty/Box	適合工具 Tool No.	備考				
				φ mm	φ d <sub>1</sub>	φ d <sub>2</sub>	B	E	L	F			t	内箱	規格該当品		
															旧国鉄	旧電電	
R1.25-2	UL	2	0.25~1.65 (22~16) (0.57~1.44)	1.7	2.5	5.5	4.5	4.5	6.7	0.8	1,000	T-112					
R1.25-3	UL	3			3.3								11.5	4.2	2,000		
R1.25-3ML	UL												14	6.7	1,000		
R1.25-3.5S	UL												11.5	4.2	2,000		
R1.25-3.5SL		3.5			3.8								5.8	14.1			
R1.25-3.5	UL												6.6	14.5	6.7		
R1.25-4S	UL	4			4.4								8.0	15.7	7.2		
R1.25-4	UL												5.4	8.0			
R1.25-5	UL	5			5.4								8.0	15.7	7.2		
R1.25-6	UL	6			6.6								12.0	21.2	10.7		
R1.25-8	UL	8			8.6								12.0	21.2	10.7	500	
R1.25-10	UL	10	10.6	13.5	24.7	13.4	300										
R2-2S		2	1.04~2.63 (16~14) (1.14~1.82)	2.3	2.5	5.5	4.5	4.5	7.2	0.85	1,000	T-112					
R2-3SL	UL	3			3.3								11.0	3.7			
R2-3	UL												14.5	7.2			
R2-3.5S	UL												6.5	12.0	4.2		
R2-3.5SL		3.5			3.8								5.8	15.2			
R2-3.5	UL												6.6	15.6	7.8		
R2-4S	UL	4			4.4								8.5	16.0	7.2		
R2-4	UL												5.4	9.5	16.5		
R2-5	UL	5			5.4								9.5	16.5	7.2		
R2-6	UL	6			6.6								12.0	21.5	11.0	500	
R2-8	UL	8			8.6								12.0	21.5	11.0		
R2-10	UL	10			10.6								13.5	25.0	13.7	300	
R2-12		12			13.2								19.0	29.4	15.4	250	
R3.5-3.5	UL	3.5			2.63~4.6 (13~11) (1.82~2.4)								3.0	3.8	8.0	6.0	6.0
R3.5-4	UL	4	4.4	17.7													
R3.5-5S	UL	5	5.4	19.0		8.2											
R3.5-5	UL			9.6													
R3.5-6S	UL	6	6.6	12.0		21.0	9.0	500									
R3.5-6	UL					21.0	9.0										
R5.5-3.5	UL	3.5	2.63~6.64 (12~10) (1.82~2.89)	3.4	3.8	6.5	6.5	6.5	12.5	1.0	1,000	T-112					
R5.5-4S	UL	4			4.4								7.0	15.2	5.2		
R5.5-4SL													8.0	17.7			
R5.5-4	UL												9.5	18.5	7.2		
R5.5-5S	UL	5			5.4								8.0	17.7			
R5.5-5	UL												9.5	18.5			
R5.5-5L	UL												12.0	25.0	12.5		
R5.5-6	UL	6			6.6								12.0	25.0	12.5		
R5.5-8	UL	8			8.6								15.0	28.0	14.0	500	
R5.5-10	UL	10			10.7								15.0	28.0	14.0		
R5.5-12	UL	12			13.2								19.0	31.8	15.8	300	
R5.5-16	UL	16			17.2								32.0	47.5	25.0	100	