


裸端子 丸形 (R形) [R8~R38]



品番 Catalog No.	規格 Standards	適合ねじ径 Stud Size	適合電線範囲 Wire Size	寸法 (mm) Dimensions							入り数 Qty/Box	適合工具 Tool No.	備考																															
		φ mm	mm ² (AWG#) (φ mm)	φ d ₁	φ d ₂	B	E	L	F	t	内箱		規格該当品																															
													旧国鉄	旧電電																														
R8-4S		4	6.64~10.52 (8) (2.89~3.65)	4.5	4.3	9.5	8.1	22.3	9.4	1.2	500	T-122 H-104N (NH-12) ※オプション ダイス使用																																
R8-4	UL				4.4	12.0		23.5										8-A-4																										
R8-5S		5			6.64~10.52 (8) (2.89~3.65)	4.5		5.3					9.5	8.1	22.3	9.4	1.2	500	T-122 H-104N (NH-12) ※オプション ダイス使用																									
R8-5	UL							5.4					12.0		23.5									SS8-5	8-A-5																			
R8-6S		6						6.64~10.52 (8) (2.89~3.65)					4.5		6.4					9.5	8.1	22.3	9.4	1.2	500	T-122 H-104N (NH-12) ※オプション ダイス使用																		
R8-6	UL								6.6		12.0				23.5														SS8-6	8-A-6														
R8-6L		6							6.64~10.52 (8) (2.89~3.65)		4.5				4.5					9.5		8.1					22.3	9.4	1.2	300	T-122 H-104N (NH-12) ※オプション ダイス使用													
R8-8	UL															8.6		15.0														29.5	13.9				SS8-8	8-A-8						
R8-10	UL	10														6.64~10.52 (8) (2.89~3.65)		4.5														10.7	9.5	8.1	22.3	9.4	1.2	300	T-122 H-104N (NH-12) ※オプション ダイス使用					
R8-12	UL	12																					13.2		32.0							48.5								24.4				SS8-10
R8-16	UL	16	17.2	32.0			48.5			24.4																														8-A-12	8-A-16			
R14-5S		5	10.52~16.78 (6) (3.65~4.62)	5.8			5.4			10.0		10.0											28.5		13.5			1.5		500		H-104N (NH-12) ※オプション ダイス使用												
R14-5	UL				5.4	12.0	29.5																																	SS14-5	14-A-5			
R14-6S		6			10.52~16.78 (6) (3.65~4.62)	5.8	5.8			10.0				28.5			13.5		1.5				500													H-104N (NH-12) ※オプション ダイス使用								
R14-6	UL							6.6					12.0								29.5																					SS14-6	14-A-6	
R14-6L		6						10.52~16.78 (6) (3.65~4.62)					5.8								5.8			10.0		28.5												13.5		1.5	500	H-104N (NH-12) ※オプション ダイス使用		
R14-8S									8.6		12.0				29.5					13.5										SS14-8	14-A-8													
R14-8	UL	8							10.52~16.78 (6) (3.65~4.62)		5.8				5.8					10.0		28.5			13.5		1.5		500	H-104N (NH-12) ※オプション ダイス使用														
R14-10	UL	10														10.7	16.0	32.7					14.7												SS14-10		14-A-10							
R14-12	UL	12														13.2	22.0	41.0					20.0														SS14-12		14-A-12					
R14-16	UL	16														17.2	32.0	51.0					25.0															14-A-16						
R22-5S		5	16.78~26.66 (4) (4.62~5.81)	7.7								7.7				11.5	14.0	13.2					1.8					300			H-104N (NH-12) ※オプション ダイス使用													
R22-5	UL																								5.4				16.5			33.0	13.3						SS22-5		22-A-5			
R22-6S		6			16.78~26.66 (4) (4.62~5.81)	7.7	7.7			11.5				14.0					13.2						1.8				300			H-104N (NH-12) ※オプション ダイス使用												
R22-6	UL																																6.6	16.5	33.0	13.2							SS22-6	22-A-6
R22-6L		6						16.78~26.66 (4) (4.62~5.81)					7.7								7.7			11.5		14.0							13.2	1.8	300	H-104N (NH-12) ※オプション ダイス使用								
R22-8S																		8.6										17.5									38.0	17.7					SS22-8	22-A-8
R22-8	UL	8							16.78~26.66 (4) (4.62~5.81)		7.7				7.7			11.5		14.0		13.2					1.8	300		H-104N (NH-12) ※オプション ダイス使用														
R22-10	UL	10																	16.5										33.0								13.2					SS22-10	22-A-10	
R22-12	UL	12																	17.5										38.0								17.7						SS22-12	22-A-12
R22-16	UL	16																	17.2										32.0				52.5		25.0							22-A-16		
R38-5		5	26.66~42.42 (2) (5.81~7.34)	9.4								9.4				13.2	16.0		17.3				1.9						200		H-104N (NH-12) (NH-21) ※オプション ダイス使用													
R38-6SS																						5.4						13.5					30.7		10.8									
R38-6	UL	6			26.66~42.42 (2) (5.81~7.34)	9.4	9.4			13.2				16.0								17.3			1.9			200				H-104N (NH-12) (NH-21) ※オプション ダイス使用												
R38-8S		6.6																															16.0		38.5		17.3						38-A-6	
R38-8	UL	8						26.66~42.42 (2) (5.81~7.34)					9.4								9.4			13.2		16.0							17.3	1.9	150	H-104N (NH-12) (NH-21) ※オプション ダイス使用								
R38-10S		8.6																	22.0										42.0								17.8						SS38-8	38-A-8
R38-10	UL	10							26.66~42.42 (2) (5.81~7.34)		9.4				9.4			13.2	16.0	17.3							1.9		200	H-104N (NH-12) (NH-21) ※オプション ダイス使用														
R38-12	UL	12																				10.7						22.0									38.5	17.3					SS38-10	38-A-10
R38-16	UL	16																				13.2						22.0									42.0	17.8						SS38-12
																						26.66~42.42 (2) (5.81~7.34)						9.4					9.4		13.2		32.0	33.8	1.9	100	H-104N (NH-12) (NH-21) ※オプション ダイス使用			
			17.2	32.0								63.0				33.8																												38-A-16