


裸端子 丸形 (R形) [R8~R38]



品番 Catalog No.	規格 Standards	適合ねじ径 Stud Size	適合電線範囲 Wire Size	寸法 (mm) Dimensions							入り数 Qty/Box	適合工具 Tool No.	備考	
		φ mm	mm ² (AWG#) (φ mm)	φ d ₁	φ d ₂	B	E	L	F	t	内箱		規格該当品	
													旧国鉄	旧電電
R8-4S		4	6.64~10.52 (8) (2.89~3.65)	4.5	4.3	9.5	8.1	22.3	9.4	1.2	500	T-122 H-104N (NH-12) ※オプション ダイス使用		
R8-4	UL				4.4	12.0		23.5						
R8-5S		5			5.3	9.5		22.3						
R8-5	UL				5.4	12.0		23.5						
R8-6S		6			6.4	9.5		22.3						
R8-6	UL				6.6	12.0		23.5						
R8-6L		8			8.6	15.0		29.5	13.9				300	
R8-8	UL				10.7									
R8-10	UL	10			13.2	32.0		48.5	24.4				100	
R8-12	UL	12			17.2									
R8-16	UL	16												
R14-5S		5	10.52~16.78 (6) (3.65~4.62)	5.8	5.4	10.0	10.0	28.5	13.5	1.5	500	H-104N (NH-12) ※オプション ダイス使用		
R14-5	UL				5.4	12.0		29.5						
R14-6S		6			6.6	10.0		28.5						
R14-6	UL				6.6	12.0		29.5						
R14-6L		8			6.6	16.0		32.7	14.7					
R14-8S					8.6	12.0		29.5	13.5					
R14-8	UL	10			10.7	16.0		32.7	14.7					
R14-10	UL	12			13.2	22.0		41.0	20.0				300	
R14-12	UL	16			17.2	32.0		51.0	25.0				200	
R14-16	UL													
R22-5S		5	16.78~26.66 (4) (4.62~5.81)	7.7	5.4	14.0	11.5	33.0	13.2	1.8	300	H-104N (NH-12) ※オプション ダイス使用		
R22-5	UL				5.4	16.5			13.3					
R22-6S		6			6.6	14.0		13.2						
R22-6	UL				6.6	16.5		13.2						
R22-6L		8			6.6	17.5		38.0	17.7					250
R22-8S					8.6	14.0		33.0	13.3				300	
R22-8	UL	10			10.7	16.5		33.0	13.2					
R22-10	UL	12			13.2	17.5		38.0	17.7				250	
R22-12	UL	16			17.2	22.0		42.0	19.5				200	
R22-16	UL				32.0			52.5	25.0				100	
R38-5		5	26.66~42.42 (2) (5.81~7.34)	9.4	5.4	16.0	13.2	38.5	17.3	1.9	200	H-104N (NH-12) (NH-21) ※オプション ダイス使用		
R38-6SS					6.4	13.5			10.8					
R38-6	UL	6.6			16.0	17.3								
R38-8S	UL	8			8.6	22.0		42.0	17.8					150
R38-8	UL	10			10.7	16.0		38.5	17.3					200
R38-10S		12			13.2	22.0		42.0	17.8				150	
R38-10	UL				17.2	32.0		63.0	33.8				100	
R38-12	UL	16												
R38-16	UL													